

## LOBADUR<sup>®</sup> WS 2K Contact

### Waterborne 2- Component Adhesive Primer for Re-Finishing of Pre-Finished Parquet without Intermediate Sanding

Article No.: 11520  
Package Size: 0,5kg mass and 0,25kg hardener combined package  
Giscode: W3/DD

**Range of Use:** Waterborne adhesive primer for the re-finishing of newly layed, finished, pre-finished parquet **without intermediate sanding.**  
Suitable for the belated achievement of new surface characteristics, such as edge protection, changes in the gloss level, anti-slipping according to DIN 18032 or BGR 181, yellowing protection of light wood by using LOBADUR<sup>®</sup> WS UV-Protect

**Usage Information:**

- Shake mass, add hardener at a ratio of 2 : 1 and mix it by shaking.
- After mixing able to use for 2 hours.
- Because of the arising over pressure, do not store already mixed material in closed packages

**Set-up Recommendations for UV-Finished Pre-Finished Parquet:**

1. Thoroughly dust factory finished parquet, clean off any remaining dirt. An intermediate sanding is not necessary.
2. Apply one coat of LOBADUR<sup>®</sup> WS2K Contact by using a trowel
3. After non-adhesive drying (ca. 2 hours) apply LOBADUR<sup>®</sup> WS 2K Supra, LOBADUR<sup>®</sup> WS 2K Duo
4. Due to the variety of possible surfaces an adesion test or a consultation with the LOBA technical usage department is necessary.

**Covering Tool:** LOBATOOL stainless trowel

**Covering Quantity:** Ca. 10 g/m<sup>2</sup> (100 m<sup>2</sup>/kg) 1g / square foot, 1 combined package sufficient for ca. 70m<sup>2</sup>

**Drying Time:** Earliest possible re-finishing after 2 hours (await non-adhesive drying), however within 24 hours.

**Thinner:** The primer is ready-to-use and cannot be diluted!

**Storage and Transportation:** +5 to +25°C( 41 °F to 77°F), storable for 12 months  
Hardener contains Isocyanate, Xi irritend not a hazardous material according to ADR

**The general information on the use of LOBADUR<sup>®</sup> WS products must be noticed.**

LOBA GmbH & Co. KG  
Tel: +49 (0) 7156 357 220  
Fax: + 49 (0) 7156 357 211  
Mail: [service@loba.de](mailto:service@loba.de)

prepared : 27.01.2008 DK