

LOBADUR® WS EasyFillPlus

**Waterborne, fast drying binder based on acrylate
for the production of wood putty.**

Article No.: 11038
Gloss level: n/a
Package Size: 5l, 1l
Giscode: W 2 / substitute product according to TRGS 617
Solids: 20 ± 1%
Viscosity DIN 4: Not defined

Range of Use: Usable for the filling of joints and minor damages on parquet and hardwood floors. Floors which are nailed or screwed are normally not filled with putty. Dry wood putty could partially break loose. After drying it will turn into a wood putty mass with great filling capability and excellent adhesion.

Information on Use:

- Shake material well
- Mix LOBADUR® WS EasyFillPlus with very fine wood dust from sanding into a smooth mass
- The finer the dusting sand, the easier it will be to trowel- fill the mass and there will also be a better adhesion in the joints
- Trowel-fill the complete floor before the final cut. Repeat procedure on larger joints or damages after drying.
- Thoroughly peel all remains off of surface
- Completely sand off all putty from area (final cut)

Setup Recommendations:

1. Sand with coarse and medium sanding paper (e.g. grade 36 , grade 60)
2. Trowel-fill with putty
3. Drying
4. Final Cut (e.g. grade 100 / 120)
5. Surface treatment

Parquet and Hard wood Floors:

Covering Tool: LOBATOOL stainless trowel

Covering Quantity: On newly layed parqet with small joints ca. 50ml/m² (20m²/l), 5 ml / square foot

Drying Time: Depending on the size of the joints, able to sand within one to two hours. Retreatment with waterborne LOBADUR®-Systemen after a minimum of 2 hours. Retreatment with solvent based LOBADUR® Systemen, for example, LOBASOL® Öl-Systemen after a complete drying over night.

Possible Surface Treatment with: All waterborne LOBADUR® Lacksysteme without limitation
All solvent based LOBADUR® Lacksysteme after complete drying
All LOBASOL® Öl-Systeme after complete drying

Thinner: The primer is ready-to-use and cannot be diluted!

Storage and Transportation: +5°C to +25°C (41°F to 77°F), storable for 12 months, not a hazardous material according to ADR

**The general Information on the Use of LOBADUR® WS
Products are part of this Informatin and must be noticed.**

LOBA GmbH & Co. KG
Tel: +49 (0) 7156 357 169
Fax: + 49 (0) 7156 357 211
Mail: service@loba.de